



Woven Resin Brake Lining Rolls

Non-Asbestos

For Tractor, Agricultural and Engineering Machine

Specification:
Length: ≤20 meters, Thickness: 5mm ~ 30mm,
Width: 30mm ~ 550mm
Color: yellow, brown

Has high temperature wear resistance, low wear rate and stable friction coefficient.

GRT-01 Reddish



GRT-02 Yellow



GRT-03 Grinded



Temperature	Coefficient of friction(μ)	Wear rate(v) ($\text{cm}^3/\text{N}\cdot\text{m}$)
100℃	0.35~0.65	$\leq 0.7 \times 10^{-7}$
150℃	0.35~0.65	$\leq 1.1 \times 10^{-7}$
200℃	0.30~0.60	$\leq 1.5 \times 10^{-7}$

The products belong to the structure of integrative full woven type, which are made of selected fiber as reinforced materials, oil-soluble phenol resin as adhesive by the process of knitting, pickling, baking in oven and grinding.

JIANGSU GREAT INDUSTRIALS GROUP CORP.LTD

TEL:Tel: (86515) 89908899 ,89908077 FAX:0086 515 89908889

E-mail: victor18@chinagreatcorp.com ; katrina@great-industrials.com ; sales02@great-industrials.com

www.chinagreatcorp.com www.greatautos.cn

Head office:

8th Floor, Bldg 1, SF Industrial Park, No. 787 Yandu Road, Yandu District, Yancheng, Jiangsu